

ARDEX WA HARDENER A

Chemwatch Material Safety Data Sheet
Issue Date: 20-Feb-2009
NC317ECP

CHEMWATCH 16-3321
Version No:3
CD 2008/4 Page 1 of 18

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

ARDEX WA HARDENER A

SYNONYMS

"epoxy grout"

PROPER SHIPPING NAME

AMINES, LIQUID, CORROSIVE, N.O.S. or POLYAMINES, LIQUID, CORROSIVE, N.O.S.(contains triethylenetetramine and diethylenetriamine)

PRODUCT USE

Epoxy grout (two part) used for grouting wall and floor tiles.

SUPPLIER

Company: Ardex Australia Pty Ltd

Address:

20 Powers Road

Seven Hills

NSW, 2147

AUS

Telephone: 1800 224 070


Fax: +61 2 9838 7817

Section 2 - HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE

HAZARDOUS SUBSTANCE. DANGEROUS GOODS. According to the Criteria of NOHSC, and the ADG Code.

CHEMWATCH HAZARD RATINGS



POISONS SCHEDULE

S5

RISK

- » Harmful in contact with skin and if swallowed.
- » Causes burns.
- » Risk of serious damage to eyes.
- » May cause SENSITISATION by skin contact.

SAFETY

- » Keep locked up.
- » Avoid exposure - obtain special instructions before use.
- » To clean the floor and all objects contaminated by this material use water and detergent.
- » Take off immediately all contaminated clothing.
- » In case of accident or if you feel unwell IMMEDIATELY contact Doctor or Poisons Information Centre (show label if

continued...

ARDEX WA HARDENER A

Chemwatch Material Safety Data Sheet
Issue Date: 20-Feb-2009
NC317ECP

CHEMWATCH 16-3321
Version No:3
CD 2008/4 Page 2 of 18
Section 2 - HAZARDS IDENTIFICATION

possible).
» This material and its container must be disposed of as hazardous waste.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
triethylenetetramine	112-24-3	2.5-10
diethylenetriamine	111-40-0	2.5-10

Section 4 - FIRST AID MEASURES

SWALLOWED

- For advice, contact a Poisons Information Centre or a doctor at once.
- Urgent hospital treatment is likely to be needed.
- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
- Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
- Transport to hospital or doctor without delay.

EYE

- » If this product comes in contact with the eyes:
- Immediately hold eyelids apart and flush the eye continuously with running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.
- Transport to hospital or doctor without delay.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

- » If skin or hair contact occurs:
- Immediately flush body and clothes with large amounts of water, using safety shower if available.
- Quickly remove all contaminated clothing, including footwear.
- Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre.
- Transport to hospital, or doctor.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- Transport to hospital, or doctor.
- Inhalation of vapours or aerosols (mists, fumes) may cause lung oedema.
- Corrosive substances may cause lung damage (e.g. lung oedema, fluid in the lungs).
- As this reaction may be delayed up to 24 hours after exposure, affected individuals need complete rest (preferably in semi-recumbent posture) and must be kept under medical observation even if no symptoms are

continued...

ARDEX WA HARDENER A

Chemwatch Material Safety Data Sheet

Issue Date: 20-Feb-2009

NC317ECP

CHEMWATCH 16-3321

Version No:3

CD 2008/4 Page 3 of 18

Section 4 - FIRST AID MEASURES

(yet) manifested.

• Before any such manifestation, the administration of a spray containing a dexamethasone derivative or beclomethasone derivative may be considered.

This must definitely be left to a doctor or person authorised by him/her.

(ICSC13719).

NOTES TO PHYSICIAN

» For acute or short-term repeated exposures to highly alkaline materials:

• Respiratory stress is uncommon but present occasionally because of soft tissue edema.

• Unless endotracheal intubation can be accomplished under direct vision, cricothyroidotomy or tracheotomy may be necessary.

• Oxygen is given as indicated.

• The presence of shock suggests perforation and mandates an intravenous line and fluid administration.

• Damage due to alkaline corrosives occurs by liquefaction necrosis whereby the saponification of fats and solubilisation of proteins allow deep penetration into the tissue.

Alkalis continue to cause damage after exposure.

INGESTION:

• Milk and water are the preferred diluents

No more than 2 glasses of water should be given to an adult.

• Neutralising agents should never be given since exothermic heat reaction may compound injury.

* Catharsis and emesis are absolutely contra-indicated.

* Activated charcoal does not absorb alkali.

* Gastric lavage should not be used.

Supportive care involves the following:

• Withhold oral feedings initially.

• If endoscopy confirms transmucosal injury start steroids only within the first 48 hours.

• Carefully evaluate the amount of tissue necrosis before assessing the need for surgical intervention.

• Patients should be instructed to seek medical attention whenever they develop difficulty in swallowing (dysphagia).

SKIN AND EYE:

• Injury should be irrigated for 20-30 minutes.

Eye injuries require saline. [Ellenhorn & Barceloux: Medical Toxicology].

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

• Foam.

• Dry chemical powder.

• BCF (where regulations permit).

• Carbon dioxide.

• Water spray or fog - Large fires only.

FIRE FIGHTING

• Alert Fire Brigade and tell them location and nature of hazard.

• Wear full body protective clothing with breathing apparatus.

• Prevent, by any means available, spillage from entering drains or water course.

• Use fire fighting procedures suitable for surrounding area.

• Do not approach containers suspected to be hot.

• Cool fire exposed containers with water spray from a protected location.

• If safe to do so, remove containers from path of fire.

• Equipment should be thoroughly decontaminated after use.

When any large container (including road and rail tankers) is involved in a fire, consider evacuation by 800 metres in all directions.

FIRE/EXPLOSION HAZARD

» Combustible. Will burn if ignited.

Combustion products include: carbon monoxide (CO), carbon dioxide (CO₂), nitrogen oxides (NO_x),

continued...

ARDEX WA HARDENER A

Chemwatch Material Safety Data Sheet

Issue Date: 20-Feb-2009

NC317ECP

CHEMWATCH 16-3321

Version No:3

CD 2008/4 Page 4 of 18

Section 5 - FIRE FIGHTING MEASURES

pyrolysis products typical of burning organic material.

May emit corrosive fumes.

FIRE INCOMPATIBILITY

- Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

HAZCHEM: 2X

Personal Protective Equipment

Gas tight chemical resistant suit.

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES

MINOR SPILLS

- Clean up all spills immediately.
- Avoid breathing vapours/ aerosols/ or dusts and avoid contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb spill with sand, earth, inert material or vermiculite.
- Place in a suitable, labelled container for waste disposal.

MAJOR SPILLS

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- Wear full body protective clothing with breathing apparatus.
- Prevent, by any means available, spillage from entering drains or water course.
- Consider evacuation (or protect in place).
- Stop leak if safe to do so.
- Contain spill with sand, earth or vermiculite.
- Collect recoverable product into labelled containers for recycling.
- Neutralise/decontaminate residue.
- Collect solid residues and seal in labelled drums for disposal.
- Wash area and prevent runoff into drains.
- After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using.
- If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Avoid contact with moisture.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately. Launder contaminated clothing before re-use.

continued...

ARDEX WA HARDENER A

Chemwatch Material Safety Data Sheet

Issue Date: 20-Feb-2009

NC317ECP

CHEMWATCH 16-3321

Version No:3

CD 2008/4 Page 5 of 18

Section 7 - HANDLING AND STORAGE

- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

SUITABLE CONTAINER

» For low viscosity materials

- Drums and jerricans must be of the non-removable head type.
- Where a can is to be used as an inner package, the can must have a screwed enclosure.

For materials with a viscosity of at least 2680 cSt. (23 deg. C) and solids (between 15 C deg. and 40 deg C.):

- Removable head packaging;
 - Cans with friction closures and
 - low pressure tubes and cartridges
- may be used.

-

Where combination packages are used, and the inner packages are of glass, porcelain or stoneware, there must be sufficient inert cushioning material in contact with inner and outer packages unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic.

STORAGE INCOMPATIBILITY

- Avoid contact with copper, aluminium and their alloys.
- Avoid strong acids, acid chlorides and acid anhydrides..
- Avoid reaction with oxidising agents.

STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.
- DO NOT store near acids, or oxidising agents.
- No smoking, naked lights, heat or ignition sources.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

Source	Material	TWA ppm	TWA mg/m ³
Australia Exposure Standards	diethylenetriamine (Diethylene triamine)	1	4.2

The following materials had no OELs on our records

- triethylenetetramine:

CAS:112- 24- 3

MATERIAL DATA

» Not available. Refer to individual constituents.

INGREDIENT DATA

DIETHYLENETRIAMINE:

TRIETHYLENETETRAMINE:

» Sensory irritants are chemicals that produce temporary and undesirable side-effects on the eyes, nose or throat. Historically occupational exposure standards for these irritants have been based on observation of workers' responses to various airborne concentrations. Present day expectations require that nearly every individual should be protected against even minor sensory irritation and exposure standards are established

continued...

ARDEX WA HARDENER A

Chemwatch Material Safety Data Sheet
Issue Date: 20-Feb-2009
NC317ECP

CHEMWATCH 16-3321
Version No:3
CD 2008/4 Page 6 of 18

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

using uncertainty factors or safety factors of 5 to 10 or more. On occasion animal no-observable-effect-levels (NOEL) are used to determine these limits where human results are unavailable. An additional approach, typically used by the TLV committee (USA) in determining respiratory standards for this group of chemicals, has been to assign ceiling values (TLV C) to rapidly acting irritants and to assign short-term exposure limits (TLV STELs) when the weight of evidence from irritation, bioaccumulation and other endpoints combine to warrant such a limit. In contrast the MAK Commission (Germany) uses a five-category system based on intensive odour, local irritation, and elimination half-life. However this system is being replaced to be consistent with the European Union (EU) Scientific Committee for Occupational Exposure Limits (SCOEL); this is more closely allied to that of the USA.

OSHA (USA) concluded that exposure to sensory irritants can:

- cause inflammation
- cause increased susceptibility to other irritants and infectious agents
- lead to permanent injury or dysfunction
- permit greater absorption of hazardous substances and
- acclimate the worker to the irritant warning properties of these substances thus increasing the risk of overexposure.

TRIETHYLENETETRAMINE:

CEL TWA: 1 ppm, 6 mg/m³; STEL: 2 ppm, 12 mg/m³
[compare OEL TWA (Sweden): 1 ppm, 6 mg/m³; STEL: 2 ppm, 12 mg/m³ Sensitiser]

PERSONAL PROTECTION

EYE

- Chemical goggles.
- Full face shield may be required for supplementary but never for primary protection of eyes
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

HANDS/FEET

» NOTE:

- The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.
- Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.
- When handling liquid-grade epoxy resins wear chemically protective gloves (e.g nitrile or nitrile-butadiene rubber), boots and aprons.
- DO NOT use cotton or leather (which absorb and concentrate the resin), polyvinyl chloride, rubber or polyethylene gloves (which absorb the resin).
- DO NOT use barrier creams containing emulsified fats and oils as these may absorb the resin; silicone-based barrier creams should be reviewed prior to use.
- Leather wear not recommended: Contaminated leather footwear, watch bands, should be destroyed, i.e. burnt, as they cannot be adequately decontaminated.

OTHER

- Overalls.
- PVC Apron.
- PVC protective suit may be required if exposure severe.
- Eyewash unit.
- Ensure there is ready access to a safety shower.

continued...

ARDEX WA HARDENER A

Chemwatch Material Safety Data Sheet
Issue Date: 20-Feb-2009
NC317ECP

CHEMWATCH 16-3321
Version No:3
CD 2008/4 Page 7 of 18

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

RESPIRATOR

» Respiratory protection is required when ANY "Worst Case" vapour-phase concentration is exceeded (see Computer Prediction in "Exposure Standards").

Protection Factor (Min)	Half- Face Respirator	
Full- Face Respirator	10 x ES	AK- P- - AUS
	-	-
AK- P- - PAPR- AUS		-
50 x ES	-	-
AK- P- - AUS		-
	AK- P- - PAPR- AUS	100 x ES
-		AK- P- - 2
	-	

^ - Full-face.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required. For further information consult site specific CHEMWATCH data (if available), or your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

» General exhaust is adequate under normal operating conditions. Local exhaust ventilation may be required in special circumstances. If risk of overexposure exists, wear approved respirator. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection. Provide adequate ventilation in warehouses and enclosed storage areas.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Coloured strongly alkaline paste with an amine like odour; emulsifiable in water.

PHYSICAL PROPERTIES

Corrosive.
Alkaline.

Molecular Weight: Not Applicable
Melting Range (°C): Not Available
Solubility in water (g/L): Partly Miscible
pH (1% solution): Not Available
Volatile Component (%vol): Not Available
Relative Vapour Density (air=1): Not Available
Lower Explosive Limit (%): Not Available
Autoignition Temp (°C): 335
State: Non Slump Paste

Boiling Range (°C): Not Available
Specific Gravity (water= 1): 1.7
pH (as supplied): 13
Vapour Pressure (kPa): Not Available
Evaporation Rate: Not Available
Flash Point (°C): 135
Upper Explosive Limit (%): Not Available
Decomposition Temp (°C): Not Available
Viscosity: Not Available

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

For incompatible materials - refer to Section 7 - Handling and Storage.

continued...

ARDEX WA HARDENER A

Chemwatch Material Safety Data Sheet
Issue Date: 20-Feb-2009
NC317ECP

CHEMWATCH 16-3321
Version No:3
CD 2008/4 Page 8 of 18

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

» Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual. The material can produce chemical burns within the oral cavity and gastrointestinal tract following ingestion. Amines without benzene rings when swallowed are absorbed throughout the gut. Corrosive action may cause damage throughout the gastrointestinal tract. They are removed through the liver, kidney and intestinal mucosa by enzyme breakdown.

EYE

» The material can produce chemical burns to the eye following direct contact. Vapours or mists may be extremely irritating. If applied to the eyes, this material causes severe eye damage. Vapours of volatile amines irritate the eyes, causing excessive secretion of tears, inflammation of the conjunctiva and slight swelling of the cornea, resulting in "halos" around lights. This effect is temporary, lasting only for a few hours. However this condition can reduce the efficiency of undertaking skilled tasks, such as driving a car. Direct eye contact with liquid volatile amines may produce eye damage, permanent for the lighter species.

SKIN

» Skin contact with the material may be harmful; systemic effects may result following absorption. The material can produce chemical burns following direct contact with the skin. Volatile amine vapours produce irritation and inflammation of the skin. Direct contact can cause burns. They may be absorbed through the skin and cause similar effects to swallowing, leading to death. The skin may exhibit whiteness, redness and wheals. Open cuts, abraded or irritated skin should not be exposed to this material. Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

INHALED

» The material is not thought to produce adverse health effects following inhalation (as classified by EC Directives using animal models). Nevertheless, adverse systemic effects have been produced following exposure of animals by at least one other route and good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.

CHRONIC HEALTH EFFECTS

» Repeated or prolonged exposure to corrosives may result in the erosion of teeth, inflammatory and ulcerative changes in the mouth and necrosis (rarely) of the jaw. Bronchial irritation, with cough, and frequent attacks of bronchial pneumonia may ensue. Gastrointestinal disturbances may also occur. Chronic exposures may result in dermatitis and/or conjunctivitis. Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population. There has been some concern that this material can cause cancer or mutations but there is not enough data to make an assessment. Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. There is some evidence that inhaling this product is more likely to cause a sensitisation reaction in some persons compared to the general population. Exposure to the material for prolonged periods may cause physical defects in the developing embryo (teratogenesis). Ample evidence exists, from results in experimentation, that developmental disorders are directly caused by human exposure to the material.

continued...

ARDEX WA HARDENER A

Chemwatch Material Safety Data Sheet
Issue Date: 20-Feb-2009
NC317ECP

CHEMWATCH 16-3321
Version No:3
CD 2008/4 Page 9 of 18
Section 11 - TOXICOLOGICAL INFORMATION

TOXICITY AND IRRITATION

» unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

» Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested.

Handling ethyleneamine products is complicated by their tendency to react with other chemicals, such as carbon dioxide in the air, which results in the formation of solid carbamates. Because of their ability to produce chemical burns, skin rashes, and asthma-like symptoms, ethyleneamines also require substantial care in handling. Higher molecular weight ethyleneamines are often handled at elevated temperatures further increasing the possibility of vapor exposure to these compounds.

Because of the fragility of eye tissue, almost any eye contact with any ethyleneamine may cause irreparable damage, even blindness. A single, short exposure to ethyleneamines, may cause severe skin burns, while a single, prolonged exposure may result in the material being absorbed through the skin in harmful amounts. Exposures have caused allergic skin reactions in some individuals. Single dose oral toxicity of ethyleneamines is low. The oral LD50 for rats is in the range of 1000 to 4500 mg/kg for the ethyleneamines.

In general, the low-molecular weight polyamines have been positive in the Ames assay, increase sister chromatid exchange in Chinese hamster ovary (CHO) cells, and are positive for unscheduled DNA synthesis although they are negative in the mouse micronucleus assay. It is believed that the positive results are based on its ability to chelate copper.

Triethylenetetramine (TETA) is a severe irritant to skin and eyes and induces skin sensitisation.

TETA is of moderate acute toxicity: LD50(oral, rat) > 2000 mg/kg bw, LD50(dermal, rabbit) = 550 - 805 mg/kg bw. Acute exposure to saturated vapour via inhalation was tolerated without impairment. Exposure to aerosol leads to reversible irritations of the mucous membranes in the respiratory tract.

Following repeated oral dosing via drinking water only in mice but not in rats at concentration of 3000 ppm there were signs of impairment. The NOAEL is 600 ppm [92 mg/kg bw (oral, 90 days)]. Lifelong dermal application to mice (1.2 mg/mouse) did not result in tumour formation.

There are differing results of the genetic toxicity for TETA. The positive results of the in vitro tests may be the result of a direct genetic action as well as a result of an interference with essential metal ions. Due to this uncertainty of the in vitro tests, the genetic toxicity of TETA has to be assessed on the basis of in vivo tests.

The in vivo micronucleus tests (i.p. and oral) and the SLRL test showed negative results. There are no human data on reproductive toxicity (fertility assessment). The analogue diethylenetriamine had no effects on reproduction. TETA shows developmental toxicity in animal studies if the chelating property of the substance is effective. The NOEL is 830 mg/kg bw (oral).

Experience with female patients suffering from Wilson's disease demonstrated that no miscarriages and no foetal abnormalities occur during treatment with TETA..

In rats, there are several studies concerning developmental toxicity. The oral treatment of rats with 75, 375 and 750 mg/kg resulted in no effects on dams and fetuses, except slight increased fetal body weight. After oral treatment of rats with 830 or 1670 mg/kg bw only in the highest dose group increased foetal abnormalities in 27/44 fetus (69,2 %) were recorded, when simultaneously the copper content of the feed was reduced. Copper supplementation in the feed reduced significantly the fetal abnormalities of the highest dose group to 3/51 (6,5 % foetus. These findings suggest that the developmental toxicity

continued...

ARDEX WA HARDENER A

Chemwatch Material Safety Data Sheet

Issue Date: 20-Feb-2009

NC317ECP

CHEMWATCH 16-3321

Version No:3

CD 2008/4 Page 10 of 18

Section 11 - TOXICOLOGICAL INFORMATION

is produced as a secondary consequence of the chelating properties of TETA.

TRIETHYLENETETRAMINE:

» unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

Oral (rat) LD50: 2500 mg/kg

Dermal (rabbit) LD50: 805 mg/kg

IRRITATION

Skin (rabbit): 490 mg Open SEVERE

Skin (rabbit): 5 mg/24 SEVERE

Eye (rabbit); 49 mg - SEVERE

Eye (rabbit): 20 mg/24 h - Moderate

» Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested.

Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production.

The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

The material may cause severe skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. Repeated exposures may produce severe ulceration.

Handling ethyleneamine products is complicated by their tendency to react with other chemicals, such as carbon dioxide in the air, which results in the formation of solid carbamates. Because of their ability to produce chemical burns, skin rashes, and asthma-like symptoms, ethyleneamines also require substantial care in handling. Higher molecular weight ethyleneamines are often handled at elevated temperatures further increasing the possibility of vapor exposure to these compounds.

Because of the fragility of eye tissue, almost any eye contact with any ethyleneamine may cause irreparable damage, even blindness. A single, short exposure to ethyleneamines, may cause severe skin burns, while a single, prolonged exposure may result in the material being absorbed through the skin in harmful amounts. Exposures have caused allergic skin reactions in some individuals. Single dose oral toxicity of ethyleneamines is low. The oral LD50 for rats is in the range of 1000 to 4500 mg/kg for the ethyleneamines.

In general, the low-molecular weight polyamines have been positive in the Ames assay, increase sister chromatid exchange in Chinese hamster ovary (CHO) cells, and are positive for unscheduled DNA synthesis although they are negative in the mouse micronucleus assay. It is believed that the positive results are based on its ability to chelate copper.

Triethylenetetramine (TETA) is a severe irritant to skin and eyes and induces skin sensitisation.

continued...

ARDEX WA HARDENER A

Chemwatch Material Safety Data Sheet

Issue Date: 20-Feb-2009

NC317ECP

CHEMWATCH 16-3321

Version No:3

CD 2008/4 Page 11 of 18

Section 11 - TOXICOLOGICAL INFORMATION

TETA is of moderate acute toxicity: LD50(oral, rat) > 2000 mg/kg bw, LD50(dermal, rabbit) = 550 - 805 mg/kg bw. Acute exposure to saturated vapour via inhalation was tolerated without impairment. Exposure to aerosol leads to reversible irritations of the mucous membranes in the respiratory tract.

Following repeated oral dosing via drinking water only in mice but not in rats at concentration of 3000 ppm there were signs of impairment. The NOAEL is 600 ppm [92 mg/kg bw (oral, 90 days)]. Lifelong dermal application to mice (1.2 mg/mouse) did not result in tumour formation.

There are differing results of the genetic toxicity for TETA. The positive results of the in vitro tests may be the result of a direct genetic action as well as a result of an interference with essential metal ions. Due to this uncertainty of the in vitro tests, the genetic toxicity of TETA has to be assessed on the basis of in vivo tests.

The in vivo micronucleus tests (i.p. and oral) and the SLRL test showed negative results. There are no human data on reproductive toxicity (fertility assessment). The analogue diethylenetriamine had no effects on reproduction. TETA shows developmental toxicity in animal studies if the chelating property of the substance is effective. The NOEL is 830 mg/kg bw (oral).

Experience with female patients suffering from Wilson's disease demonstrated that no miscarriages and no foetal abnormalities occur during treatment with TETA..

In rats, there are several studies concerning developmental toxicity. The oral treatment of rats with 75, 375 and 750 mg/kg resulted in no effects on dams and fetuses, except slight increased fetal body weight. After oral treatment of rats with 830 or 1670 mg/kg bw only in the highest dose group increased foetal abnormalities in 27/44 fetus (69,2 %) were recorded, when simultaneously the copper content of the feed was reduced. Copper supplementation in the feed reduced significant the fetal abnormalities of the highest dose group to 3/51 (6,5 % foetus. These findings suggest that the developmental toxicity is produced as a secondary consequence of the chelating properties of TETA.

For alkyl polyamines:

The alkyl polyamines cluster consists of organic compounds containing two terminal primary amine groups and at least one secondary amine group. Typically these substances are derivatives of ethylenediamine, propylenediamine or hexanediamine. The molecular weight range for the entire cluster is relatively narrow, ranging from 103 to 232

Acute toxicity of the alkyl polyamines cluster is low to moderate via oral exposure and a moderate to high via dermal exposure. Cluster members have been shown to be eye irritants, skin irritants, and skin sensitizers in experimental animals. Repeated exposure in rats via the oral route indicates a range of toxicity from low to high hazard. Most cluster members gave positive results in tests for potential genotoxicity.

Limited carcinogenicity studies on several members of the cluster showed no evidence of carcinogenicity. Unlike aromatic amines, aliphatic amines are not expected to be potential carcinogens because they are not expected to undergo metabolic activation, nor would activated intermediates be stable enough to reach target macromolecules.

Polyamines potentiate NMDA induced whole-cell currents in cultured striatal neurons.

Exposure to the material for prolonged periods may cause physical defects in the developing embryo (teratogenesis).

DIETHYLENETRIAMINE:

» unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

Oral (rat) LD50: 1080 mg/kg

Dermal (rabbit) LD50: 1090 mg/kg

Inhalation (Rat) LC: 70 mg/m³/4h

Intraperitoneal (Rat) LD50: 74 mg/kg

Intraperitoneal (Mouse) LD50: 71 mg/kg

» Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The

IRRITATION

Skin (rabbit):500 mg Open Moderate

Skin (rabbit): 10 mg/24h - SEVERE

continued...

ARDEX WA HARDENER A

Chemwatch Material Safety Data Sheet

Issue Date: 20-Feb-2009

NC317ECP

CHEMWATCH 16-3321

Version No:3

CD 2008/4 Page 12 of 18

Section 11 - TOXICOLOGICAL INFORMATION

significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested.

Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production.

The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

The material may cause severe skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. Repeated exposures may produce severe ulceration.

Handling ethyleneamine products is complicated by their tendency to react with other chemicals, such as carbon dioxide in the air, which results in the formation of solid carbamates. Because of their ability to produce chemical burns, skin rashes, and asthma-like symptoms, ethyleneamines also require substantial care in handling. Higher molecular weight ethyleneamines are often handled at elevated temperatures further increasing the possibility of vapor exposure to these compounds.

Because of the fragility of eye tissue, almost any eye contact with any ethyleneamine may cause irreparable damage, even blindness. A single, short exposure to ethyleneamines, may cause severe skin burns, while a single, prolonged exposure may result in the material being absorbed through the skin in harmful amounts. Exposures have caused allergic skin reactions in some individuals. Single dose oral toxicity of ethyleneamines is low. The oral LD50 for rats is in the range of 1000 to 4500 mg/kg for the ethyleneamines.

In general, the low-molecular weight polyamines have been positive in the Ames assay, increase sister chromatid exchange in Chinese hamster ovary (CHO) cells, and are positive for unscheduled DNA synthesis although they are negative in the mouse micronucleus assay. It is believed that the positive results are based on its ability to chelate copper.

For alkyl polyamines:

The alkyl polyamines cluster consists of organic compounds containing two terminal primary amine groups and at least one secondary amine group. Typically these substances are derivatives of ethylenediamine, propylenediamine or hexanediamine. The molecular weight range for the entire cluster is relatively narrow, ranging from 103 to 232

Acute toxicity of the alkyl polyamines cluster is low to moderate via oral exposure and a moderate to high via dermal exposure. Cluster members have been shown to be eye irritants, skin irritants, and skin sensitisers in experimental animals. Repeated exposure in rats via the oral route indicates a range of toxicity from low to high hazard. Most cluster members gave positive results in tests for potential genotoxicity.

Limited carcinogenicity studies on several members of the cluster showed no evidence of carcinogenicity. Unlike aromatic amines, aliphatic amines are not expected to be potential carcinogens because they are not expected to undergo metabolic activation, nor would activated intermediates be stable enough to reach target macromolecules.

Polyamines potentiate NMDA induced whole-cell currents in cultured striatal neurons.

continued...

ARDEX WA HARDENER A

Chemwatch Material Safety Data Sheet

Issue Date: 20-Feb-2009

NC317ECP

CHEMWATCH 16-3321

Version No:3

CD 2008/4 Page 13 of 18

Section 11 - TOXICOLOGICAL INFORMATION

SKIN			
diethylenetriamine	Australia Exposure Standards - Skin	Notes	Sk

Section 12 - ECOLOGICAL INFORMATION

Marine Pollutant: Not Determined

» Prevent, by any means available, spillage from entering drains or water courses.

» for diethylenetriamine (DETA)

Environmental fate:

DETA is miscible with water and inherently biodegradable.

log Kow : -2.27

The material will leach into ground water and is not expected to be biodegradable. No significant degree of bioaccumulation is anticipated.

Evaporated material is expected to photodegrade following reaction with hydroxy radicals; the half-life in air is thought to be less than a day.

DETA does not form N-nitrosamines at concentrations equal to or greater than the detection limit (500 mg/L) during a 2-week incubation period in sewage or lake water samples.

The formation of N-nitrosamines from DETA in soil could not be determined with confidence utilizing the available analytical techniques

Ecotoxicity:

A large spill could be toxic to biomass in a treatment plant or could be toxic to fish.

Daphnia magna LC50: 17 mg/l *

Fish LC50: (Pimephales promelas) 332 mg/l*

Artemia salina LC50: 710 mg/l *

*[ITW Ramset / Red Head]

Ecotoxicological data indicate that at acute exposure DETA is not toxic to algae and fish but harmful to daphnids.

» for triethylenetetramine (TETA):

Environmental fate:

TETA is completely miscible with water forming an alkaline solution (pH 10 at 10 g/l). The technical product has a vapour pressure of ca. 1 Pa at 20 C. The calculated Log Pow (unprotonated form) amounts to ca. -1.4 and indicates a low potential for bioaccumulation. There are no measured Koc -values available. For ethylenediamine (CAS Nr. 107- 15-3) and diethylenetriamine (CAS Nr. 111-40- 0), Koc -values of 4766 and 19111 were measured respectively. The high adsorption is most likely due to electrostatic interaction. A comparable Koc can be expected for TETA, which would suggest a high potential for geoaccumulation.

TETA is not readily biodegradable (0% after 20 days, OECD GL 301 D; same result with adapted inoculum). Also, in a test on inherent biodegradability with industrial sludge,

TETA was not degraded (0 % DOC removal after 28 days, OECD GL 302 B). TETA has therefore to be regarded as non-biodegradable. Adsorption onto sewage sludge was not observed. In a test on hydrolysis, TETA was not found to have undergone hydrolysis after 36 days.

Direct photolysis of TETA in the hydrosphere is not to be expected (molar extinction coefficient < 10 l / (mol.cm) at > 240 nm). The half - life due to photooxidative degradation by OH-radicals in the atmosphere is estimated to be 1.7 hours. As TETA does have a low tendency to pass from water to air, this does not represent a significant removal process from the environment.

Based upon the physical-chemical and biodegradation properties of TETA, no elimination in waste water treatment plants is assumed.

Ecotoxicity:

Fish LC50 (96 h): Poecilia reticulata 570 mg/l

Other test results with Leuciscus idus and Pimephales promelas, which could not be validated, are in the same order of magnitude.

Daphnia magna EC50 (48 h): 31.1 - 33.9 mg/l (immobilisation several tests); (21 d) >3.2- <10 mg/l; NOEC 1 mg/l (immobilisation of parental organisms was the most sensitive effect parameter).

Concentrations of 293 - 7313 mg/l had no teratogenic effects on sea-urchin (Paracentrotus lividus) eggs. The larvae were most sensitive and showed delay of development at 293 mg/l

Algal Scenedesmus subspicatus EBC50 (72 h) 2.5 mg/l; EBC10 0.67 mg/l; EuC50 >= 100 mg/l; EuC10 0.95 mg/l

Effect: growth inhibition (B = biomass; u = growth rate)

continued...

ARDEX WA HARDENER A

Chemwatch Material Safety Data Sheet

Issue Date: 20-Feb-2009

NC317ECP

CHEMWATCH 16-3321

Version No:3

CD 2008/4 Page 14 of 18

Section 12 - ECOLOGICAL INFORMATION

Algal *Selenastrum capricornutum* EC50 (72 h) 20 mg/l Effect: growth inhibition (biomass) ; NOEC < 2.5 mg/l;
EC50 (96 h) 3,7 mg/l

Microorganisms *Pseudomonas fluorescens* EC0 (24 h): 500 mg/l Effect: growth inhibition (biomass)

Bird acute LD50 (18 h): redwinged blackberry >101 mg/kg.

» DO NOT discharge into sewer or waterways.

Refer to data for ingredients, which follows:

TRIETHYLENETETRAMINE:

» Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

» Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

» For alkyl polyamines:

All members of this cluster are miscible or soluble in water. The estimated value of log K_{ow}-range from 3.67 to 1.8 is consistent with the available experimental water solubilities. Vapour pressures range from 1.1x 10⁻⁶ hPa to 0.31 hPa. Estimated and experimental pK_{bs} are in a relatively narrow range of 9.68 to 10.7.

Environmental fate:

Members of this cluster are expected to have varying degrees of mobility in the soil. Low vapor pressure and Henry's Law Constants suggest that these compounds are not expected to be in the vapor phase. Modeling suggests that all members of this cluster are likely to react rapidly with photochemically produced hydroxyl radicals with half-lives on the order of an hour, but with little material in the vapor phase, it is not expected to be a predominant removal pathway for these chemicals. Experimental data and results from estimation models indicate that all members of this cluster have the potential to biodegrade aerobically under environmental conditions. Fugacity models indicate that the members of this cluster are likely to partition predominately to soil and water. All chemicals in this cluster are expected to have low environmental persistence. Measured and estimated bioconcentration factors for members of this cluster indicate a low potential for bioaccumulation.

Ecotoxicity:

Evaluation of the available experimental and estimated aquatic toxicity data indicate acute toxicity to fish is low. *Daphnia* aquatic toxicity is generally low. Algae appear to be the most sensitive organism with several members of the cluster having measured or estimated toxicity values indicative of moderate toxicity. Chronic toxicity for all cluster members is estimated; it is generally low for fish and algae, but high for *daphnia*.

» For ethyleneamines:

Adsorption of the ethyleneamines correlates closely with both the cation exchange capacity (CEC) and organic content of the soil. Soils with increased CEC and organic content exhibited higher affinities for these amines. This dependence of adsorption on CEC and organic content is most likely due to the strong electrostatic interaction between the positively charged amine and the negatively charged soil surface.

» for triethylenetetramine (TETA):

Environmental fate:

TETA is completely miscible with water forming an alkaline solution (pH 10 at 10 g/l). The technical product has a vapour pressure of ca. 1 Pa at 20 C. The calculated Log Pow (unprotonated form) amounts to ca. -1.4 and indicates a low potential for bioaccumulation. There are no measured K_{oc}-values available. For ethylenediamine (CAS Nr. 107- 15-3) and diethylenetriamine (CAS Nr. 111-40- 0), K_{oc}-values of 4766 and 19111 were measured respectively. The high adsorption is most likely due to electrostatic interaction. A comparable K_{oc} can be expected for TETA, which would suggest a high potential for geoaccumulation.

TETA is not readily biodegradable (0% after 20 days, OECD GL 301 D; same result with adapted inoculum). Also, in a test on inherent biodegradability with industrial sludge,

TETA was not degraded (0 % DOC removal after 28 days, OECD GL 302 B). TETA has therefore to be regarded as non-biodegradable. Adsorption onto sewage sludge was not observed. In a test on hydrolysis, TETA was not found to have undergone hydrolysis after 36 days.

Direct photolysis of TETA in the hydrosphere is not to be expected (molar extinction coefficient < 10 l / (mol.cm) at > 240 nm). The half - life due to photooxidative degradation by OH-radicals in the atmosphere is estimated to be 1.7 hours. As TETA does have a low tendency to pass from water to air, this does not represent a significant removal process from the environment.

Based upon the physical-chemical and biodegradation properties of TETA, no elimination in waste water treatment plants is assumed.

Ecotoxicity:

Fish LC50 (96 h): *Poecilia reticulata* 570 mg/l

continued...

ARDEX WA HARDENER A

Chemwatch Material Safety Data Sheet

Issue Date: 20-Feb-2009

NC317ECP

CHEMWATCH 16-3321

Version No:3

CD 2008/4 Page 15 of 18

Section 12 - ECOLOGICAL INFORMATION

Other test results with *Leuciscus idus* and *Pimephales promelas*, which could not be validated, are in the same order of magnitude.

Daphnia magna EC50 (48 h): 31.1 - 33.9 mg/l (immobilisation several tests); (21 d) >3.2- <10 mg/l; NOEC 1 mg/l (immobilisation of parental organisms was the most sensitive effect parameter).

Concentrations of 293 - 7313 mg/l had no teratogenic effects on sea-urchin (*Paracentrotus lividus*) eggs. The larvae were most sensitive and showed delay of development at 293 mg/l

Algal *Scenedesmus subspicatus* EBC50 (72 h) 2.5 mg/l; EBC10 0.67 mg/l; EuC50 \geq 100 mg/l; EuC10 0.95 mg/l
Effect: growth inhibition (B = biomass; u = growth rate)

Algal *Selenastrum capricornutum* EC50 (72 h) 20 mg/l Effect: growth inhibition (biomass) ; NOEC < 2.5 mg/l; EC50 (96 h) 3,7 mg/l

Microorganisms *Pseudomonas fluorescens* EC0 (24 h): 500 mg/l Effect: growth inhibition (biomass)

Bird acute LD50 (18 h): redwinged blackberry >101 mg/kg.

» Prevent, by any means available, spillage from entering drains or water courses.

DIETHYLENETRIAMINE:

» log Kow (Prager 1995): - 1.27

» Harmful to aquatic organisms.

» For alkyl polyamines:

All members of this cluster are miscible or soluble in water. The estimated value of log Kows-range from 3.67 to 1.8 is consistent with the available experimental water solubilities. Vapour pressures range from 1.1×10^{-6} hPa to 0.31 hPa. Estimated and experimental pKbs are in a relatively narrow range of 9.68 to 10.7.

Environmental fate:

Members of this cluster are expected to have varying degrees of mobility in the soil. Low vapor pressure and Henry's Law Constants suggest that these compounds are not expected to be in the vapor phase. Modeling suggests that all members of this cluster are likely to react rapidly with photochemically produced hydroxyl radicals with half-lives on the order of an hour, but with little material in the vapor phase, it is not expected to be a predominant removal pathway for these chemicals. Experimental data and results from estimation models indicate that all members of this cluster have the potential to biodegrade aerobically under environmental conditions. Fugacity models indicate that the members of this cluster are likely to partition predominately to soil and water. All chemicals in this cluster are expected to have low environmental persistence. Measured and estimated bioconcentration factors for members of this cluster indicate a low potential for bioaccumulation.

Ecotoxicity:

Evaluation of the available experimental and estimated aquatic toxicity data indicate acute toxicity to fish is low. *Daphnia* aquatic toxicity is generally low. Algae appear to be the most sensitive organism with several members of the cluster having measured or estimated toxicity values indicative of moderate toxicity. Chronic toxicity for all cluster members is estimated; it is generally low for fish and algae, but high for *daphnia*.

» for diethylenetriamine (DETA)

Environmental fate:

DETA is miscible with water and inherently biodegradable.

log Kow : -2.27

The material will leach into ground water and is not expected to be biodegradable. No significant degree of bioaccumulation is anticipated.

Evaporated material is expected to photodegrade following reaction with hydroxy radicals; the half-life in air is thought to be less than a day.

DETA does not form N-nitrosamines at concentrations equal to or greater than the detection limit (500 mg/L) during a 2-week incubation period in sewage or lake water samples.

The formation of N-nitrosamines from DETA in soil could not be determined with confidence utilizing the available analytical techniques

Ecotoxicity:

A large spill could be toxic to biomass in a treatment plant or could be toxic to fish.

Daphnia magna LC50: 17 mg/l *

Fish LC50: (*Pimephales promelas*) 332 mg/l*

Artemia salina LC50: 710 mg/l *

*[ITW Ramset / Red Head]

Ecotoxicological data indicate that at acute exposure DETA is not toxic to algae and fish but harmful to *daphnids*.

continued...

ARDEX WA HARDENER A

Chemwatch Material Safety Data Sheet

Issue Date: 20-Feb-2009

NC317ECP

CHEMWATCH 16-3321

Version No:3

CD 2008/4 Page 16 of 18

Section 12 - ECOLOGICAL INFORMATION

» For ethyleneamines:

Adsorption of the ethyleneamines correlates closely with both the cation exchange capacity (CEC) and organic content of the soil. Soils with increased CEC and organic content exhibited higher affinities for these amines. This dependence of adsorption on CEC and organic content is most likely due to the strong electrostatic interaction between the positively charged amine and the negatively charged soil surface.

» Prevent, by any means available, spillage from entering drains or water courses.

Section 13 - DISPOSAL CONSIDERATIONS

• Containers may still present a chemical hazard/ danger when empty.

• Return to supplier for reuse/ recycling if possible.

Otherwise:

• If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.

• Where possible retain label warnings and MSDS and observe all notices pertaining to the product.

• Recycle wherever possible.

• Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.

• Treat and neutralise at an approved treatment plant. Treatment should involve: Mixing or slurring in water; Neutralisation followed by: Burial in a licenced land-fill or Incineration in a licenced apparatus (after admixture with suitable combustible material)

• Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

Section 14 - TRANSPORTATION INFORMATION

Labels Required: CORROSIVE

HAZCHEM: 2X (ADG7)

Land Transport UNDG:

Class or division: 8 Subsidiary risk: None

UN No.: 2735 UN packing group: III

Shipping Name: AMINES, LIQUID, CORROSIVE, N.O.S. or POLYAMINES, LIQUID, CORROSIVE, N.O.S. (contains triethylenetetramine and diethylenetriamine)

Air Transport IATA:

ICAO/IATA Class: 8 ICAO/IATA Subrisk: None

UN/ID Number: 2735 Packing Group: III

Special provisions: A3

Shipping Name: AMINES, LIQUID, CORROSIVE, N.O.S. *(CONTAINS TRIETHYLENETETRAMINE AND DIETHYLENETRIAMINE)

Maritime Transport IMDG:

IMDG Class: 8 IMDG Subrisk: None

UN Number: 2735 Packing Group: III

EMS Number: F- A, S- B Special provisions: 223 274 944

Limited Quantities: 5 L Marine Pollutant: Not Determined

Shipping Name: AMINES, LIQUID, CORROSIVE, N.O.S. or POLYAMINES, LIQUID, CORROSIVE, N.O.S.(contains triethylenetetramine and diethylenetriamine)

continued...

ARDEX WA HARDENER A

Chemwatch Material Safety Data Sheet

Issue Date: 20-Feb-2009

NC317ECP

CHEMWATCH 16-3321

Version No:3

CD 2008/4 Page 17 of 18

Section 15 - REGULATORY INFORMATION

POISONS SCHEDULE: S5

REGULATIONS

Regulations for ingredients

Ardex WA Hardener A (CAS: None):

No regulations applicable

triethylenetetramine (CAS: 112-24-3) is found on the following regulatory lists;

Australia Hazardous Substances

Australia Inventory of Chemical Substances (AICS)

Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Appendix E (Part 2)

Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Appendix F (Part 3)

Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Schedule 4

Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Schedule 5

GESAMP/EHS Composite List of Hazard Profiles - Hazard evaluation of substances transported by ships

IMO IBC Code Chapter 17: Summary of minimum requirements

IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk

OECD Representative List of High Production Volume (HPV) Chemicals

diethylenetriamine (CAS: 111-40-0) is found on the following regulatory lists;

Australia Exposure Standards

Australia Hazardous Substances

Australia Inventory of Chemical Substances (AICS)

Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Appendix E (Part 2)

Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Appendix F (Part 3)

Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Schedule 5

GESAMP/EHS Composite List of Hazard Profiles - Hazard evaluation of substances transported by ships

IMO IBC Code Chapter 17: Summary of minimum requirements

IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk

OECD Representative List of High Production Volume (HPV) Chemicals

Section 16 - OTHER INFORMATION

REPRODUCTIVE HEALTH GUIDELINES

Ingredient	ORG	UF	Endpoint	CR	Adeq TLV
triethylenetetramine	2.9 mg/m ³	10	D	NA	-

» These exposure guidelines have been derived from a screening level of risk assessment and should not be construed as unequivocally safe limits. ORGS represent an 8-hour time-weighted average unless specified otherwise.

CR = Cancer Risk/10000; UF = Uncertainty factor:

TLV believed to be adequate to protect reproductive health:

LOD: Limit of detection

Toxic endpoints have also been identified as:

D = Developmental; R = Reproductive; TC = Transplacental carcinogen

Jankovic J., Drake F.: A Screening Method for Occupational Reproductive

American Industrial Hygiene Association Journal 57: 641-649 (1996).

EXPOSURE STANDARD FOR MIXTURES

» "Worst Case" computer-aided prediction of vapour components/concentrations:

» Composite Exposure Standard for Mixture (TWA) (mg/m³): 6 mg/m³

» If the breathing zone concentration of ANY of the components listed below is exceeded, "Worst Case" considerations deem the individual to be overexposed.

Component	Breathing Zone ppm	Breathing Zone mg/m ³	Mixture Conc: (%)
Component	Breathing zone (ppm)	Breathing zone (mg/m ³)	Mixture Conc (%)
triethylenetetramine	1.00	6.0000	10.0

» Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature

continued...

ARDEX WA HARDENER A

Chemwatch Material Safety Data Sheet

Issue Date: 20-Feb-2009

NC317ECP

CHEMWATCH 16-3321

Version No:3

CD 2008/4 Page 18 of 18

Section 16 - OTHER INFORMATION

references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net/references.

» The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: 20-Feb-2009

Print Date: 20-Feb-2009

This is the end of the MSDS.

ARDEX WA RESIN W

Chemwatch Material Safety Data Sheet

Issue Date: 20-Feb-2009

NC317ECP

CHEMWATCH 16-3320

Version No:2.0

CD 2008/4 Page 1 of 14

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

ARDEX WA RESIN W

SYNONYMS

"epoxy grout"

PROPER SHIPPING NAME

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(contains bisphenol A/ epichlorohydrin resin)

PRODUCT USE

Epoxy grout (two part) used for grouting wall and floor tiles.

SUPPLIER

Company: Ardex Australia Pty Ltd

Address:

20 Powers Road

Seven Hills

NSW, 2147

AUS

Telephone: 1800 224 070


Fax: +61 2 9838 7817

Section 2 - HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE

HAZARDOUS SUBSTANCE. DANGEROUS GOODS. According to the Criteria of NOHSC, and the ADG Code.

CHEMWATCH HAZARD RATINGS



POISONS SCHEDULE

S5

RISK

- » May form explosive peroxides.
- » Irritating to eyes and skin.
- » May cause SENSITISATION by skin contact.
- » Toxic to aquatic organisms may cause long-term adverse effects in the aquatic environment.

SAFETY

- » Avoid exposure - obtain special instructions before use.
- » To clean the floor and all objects contaminated by this material use water and detergent.
- » This material and its container must be disposed of in a safe way.
- » In case of contact with eyes rinse with plenty of water and contact Doctor or Poisons Information Centre.
- » If swallowed IMMEDIATELY contact Doctor or

continued...

ARDEX WA RESIN W

Chemwatch Material Safety Data Sheet

Issue Date: 20-Feb-2009

NC317ECP

CHEMWATCH 16-3320

Version No:2.0

CD 2008/4 Page 2 of 14

Section 2 - HAZARDS IDENTIFICATION

Poisons Information Centre (show this container or label).

» Use appropriate container to avoid environment contamination.

» Avoid release to the environment. Refer to special instructions/ safety data sheets.

» This material and its container must be disposed of as hazardous waste.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
bisphenol A/ epichlorohydrin resin	25068-38-6	20-50
bisphenol F/ epichlorohydrin copolymer	55492-52-9	2.5-10
(C12- 14)alkylglycidyl ether	68609-97-2	2.5-10

Section 4 - FIRST AID MEASURES

SWALLOWED

- Immediately give a glass of water.
- First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

EYE

- » If this product comes in contact with the eyes:
- Wash out immediately with fresh running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- If pain persists or recurs seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

- » If skin contact occurs:
- Immediately remove all contaminated clothing, including footwear.
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Other measures are usually unnecessary.

NOTES TO PHYSICIAN

- » Treat symptomatically.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog - Large fires only.

continued...

ARDEX WA RESIN W

Chemwatch Material Safety Data Sheet

Issue Date: 20-Feb-2009

NC317ECP

CHEMWATCH 16-3320

Version No:2.0

CD 2008/4 Page 3 of 14

Section 5 - FIRE FIGHTING MEASURES

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water courses.
- Use water delivered as a fine spray to control fire and cool adjacent area.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- Equipment should be thoroughly decontaminated after use.

When any large container (including road and rail tankers) is involved in a fire, consider evacuation by 100 metres in all directions.

FIRE/EXPLOSION HAZARD

» Combustible. Will burn if ignited.

Combustion products include: carbon monoxide (CO), carbon dioxide (CO₂), aldehydes, other pyrolysis products typical of burning organic material.

FIRE INCOMPATIBILITY

- Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

HAZCHEM: ●3Z

Personal Protective Equipment

Gas tight chemical resistant suit.

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES

MINOR SPILLS

- » Environmental hazard - contain spillage.
- Clean up all spills immediately.
- Avoid contact with skin and eyes.
- Wear impervious gloves and safety goggles.
- Trowel up/scrape up.
- Place spilled material in clean, dry, sealed container.
- Flush spill area with water.

MAJOR SPILLS

- Clear area of personnel and move upwind.
 - Alert Fire Brigade and tell them location and nature of hazard.
 - Wear breathing apparatus plus protective gloves.
 - Prevent, by any means available, spillage from entering drains or water course.
 - Stop leak if safe to do so.
 - Contain spill with sand, earth or vermiculite.
 - Collect recoverable product into labelled containers for recycling.
 - Neutralise/decontaminate residue.
 - Collect solid residues and seal in labelled drums for disposal.
 - Wash area and prevent runoff into drains.
 - After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using.
 - If contamination of drains or waterways occurs, advise emergency services.
- Environmental hazard - contain spillage.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

continued...

ARDEX WA RESIN W

Chemwatch Material Safety Data Sheet

Issue Date: 20-Feb-2009

NC317ECP

CHEMWATCH 16-3320

Version No:2.0

CD 2008/4 Page 4 of 14

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- DO NOT enter confined spaces until atmosphere has been checked.
- DO NOT allow material to contact humans, exposed food or food utensils.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately. Launder contaminated clothing before re-use.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

SUITABLE CONTAINER

- Metal can or drum
- Packaging as recommended by manufacturer.
- Check all containers are clearly labelled and free from leaks.

STORAGE INCOMPATIBILITY

- Avoid reaction with amines, mercaptans, strong acids and oxidising agents.

STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

The following materials had no OELs on our records

- bisphenol A/ epichlorohydrin resin: CAS:25068- 38- 6
- bisphenol F/ epichlorohydrin copolymer: CAS:55492- 52- 9 CAS:58421- 55- 9 CAS:9003- 36- 5
- (C12- 14)alkylglycidyl ether: CAS:68609- 97- 2

MATERIAL DATA

» Sensory irritants are chemicals that produce temporary and undesirable side-effects on the eyes, nose or throat. Historically occupational exposure standards for these irritants have been based on observation of workers' responses to various airborne concentrations. Present day expectations require that nearly every individual should be protected against even minor sensory irritation and exposure standards are established using uncertainty factors or safety factors of 5 to 10 or more. On occasion animal no-observable-effect-levels (NOEL) are used to determine these limits where human results are unavailable. An additional approach, typically used by the TLV committee (USA) in determining respiratory standards for this group of chemicals, has been to assign ceiling values (TLV C) to rapidly acting irritants and to assign short-term exposure

continued...

ARDEX WA RESIN W

Chemwatch Material Safety Data Sheet

Issue Date: 20-Feb-2009

NC317ECP

CHEMWATCH 16-3320

Version No:2.0

CD 2008/4 Page 5 of 14

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

limits (TLV STELs) when the weight of evidence from irritation, bioaccumulation and other endpoints combine to warrant such a limit. In contrast the MAK Commission (Germany) uses a five-category system based on intensive odour, local irritation, and elimination half-life. However this system is being replaced to be consistent with the European Union (EU) Scientific Committee for Occupational Exposure Limits (SCOEL); this is more closely allied to that of the USA.

OSHA (USA) concluded that exposure to sensory irritants can:

- cause inflammation
- cause increased susceptibility to other irritants and infectious agents
- lead to permanent injury or dysfunction
- permit greater absorption of hazardous substances and
- acclimate the worker to the irritant warning properties of these substances thus increasing the risk of overexposure.

INGREDIENT DATA

(C12-14)ALKYLGLYCIDYL ETHER:

BISPHENOL A/ EPICHLOROHYDRIN RESIN:

BISPHENOL F/ EPICHLOROHYDRIN COPOLYMER:

» Sensory irritants are chemicals that produce temporary and undesirable side-effects on the eyes, nose or throat. Historically occupational exposure standards for these irritants have been based on observation of workers' responses to various airborne concentrations. Present day expectations require that nearly every individual should be protected against even minor sensory irritation and exposure standards are established using uncertainty factors or safety factors of 5 to 10 or more. On occasion animal no-observable-effect-levels (NOEL) are used to determine these limits where human results are unavailable. An additional approach, typically used by the TLV committee (USA) in determining respiratory standards for this group of chemicals, has been to assign ceiling values (TLV C) to rapidly acting irritants and to assign short-term exposure limits (TLV STELs) when the weight of evidence from irritation, bioaccumulation and other endpoints combine to warrant such a limit. In contrast the MAK Commission (Germany) uses a five-category system based on intensive odour, local irritation, and elimination half-life. However this system is being replaced to be consistent with the European Union (EU) Scientific Committee for Occupational Exposure Limits (SCOEL); this is more closely allied to that of the USA.

OSHA (USA) concluded that exposure to sensory irritants can:

- cause inflammation
- cause increased susceptibility to other irritants and infectious agents
- lead to permanent injury or dysfunction
- permit greater absorption of hazardous substances and
- acclimate the worker to the irritant warning properties of these substances thus increasing the risk of overexposure.

BISPHENOL A/ EPICHLOROHYDRIN RESIN:

» It is the goal of the ACGIH (and other Agencies) to recommend TLVs (or their equivalent) for all substances for which there is evidence of health effects at airborne concentrations encountered in the workplace.

At this time no TLV has been established, even though this material may produce adverse health effects (as evidenced in animal experiments or clinical experience). Airborne concentrations must be maintained as low as is practically possible and occupational exposure must be kept to a minimum.

NOTE: The ACGIH occupational exposure standard for Particles Not Otherwise Specified (P.N.O.S) does NOT apply.

BISPHENOL F/ EPICHLOROHYDRIN COPOLYMER:

» None assigned. Refer to individual constituents.

(C12-14)ALKYLGLYCIDYL ETHER:

» Odour Threshold Value for epichlorohydrin: 0.08 ppm

NOTE: Detector tubes for epichlorohydrin, measuring in excess of 5 ppm, are commercially available.

Exposure at or below the recommended TLV-TWA is thought to minimise the potential for adverse respiratory, liver, kidney effects. Epichlorohydrin has been implicated as a human skin sensitiser, hence individuals who are hypersusceptible or otherwise unusually responsive to certain chemicals may NOT be adequately protected

continued...

ARDEX WA RESIN W

Chemwatch Material Safety Data Sheet

Issue Date: 20-Feb-2009

NC317ECP

CHEMWATCH 16-3320

Version No:2.0

CD 2008/4 Page 6 of 14

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

from adverse health effects.

Odour Safety Factor(OSF)

OSF=0.54 (EPICHLOROHYDRIN).

PERSONAL PROTECTION

EYE

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

HANDS/FEET

» NOTE:

- The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.
- Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.
- When handling liquid-grade epoxy resins wear chemically protective gloves (e.g nitrile or nitrile-butadiene rubber), boots and aprons.
- DO NOT use cotton or leather (which absorb and concentrate the resin), polyvinyl chloride, rubber or polyethylene gloves (which absorb the resin).
- DO NOT use barrier creams containing emulsified fats and oils as these may absorb the resin; silicone-based barrier creams should be reviewed prior to use.

OTHER

- Overalls.
- P.V.C. apron.
- Barrier cream.
- Skin cleansing cream.
- Eye wash unit.

RESPIRATOR

» Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Breathing Zone Level ppm (volume)	Maximum Protection Factor	Half- face Respirator	Full- Face Respirator
1000	10	A- AUS P	-
1000	50	-	A- AUS P
5000	50	Airline *	-
5000	100	-	A- 2 P
10000	100	-	A- 3 P
	100+		Airline**

* - Continuous Flow

** - Continuous-flow or positive pressure demand.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required. For further information consult site specific CHEMWATCH data (if available), or your Occupational Health and Safety Advisor.

continued...

ARDEX WA RESIN W

Chemwatch Material Safety Data Sheet

Issue Date: 20-Feb-2009

NC317ECP

CHEMWATCH 16-3320

Version No:2.0

CD 2008/4 Page 7 of 14

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS

» Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection.

An approved self contained breathing apparatus (SCBA) may be required in some situations.

Provide adequate ventilation in warehouse or closed storage area.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Coloured paste with an amine like odour; emulsifiable in water.

PHYSICAL PROPERTIES

Molecular Weight: Not Applicable

Melting Range (°C): Not Available

Solubility in water (g/L): Partly Miscible

pH (1% solution): Not Available

Volatile Component (%vol): Not Available

Relative Vapour Density (air=1): Not Available

Lower Explosive Limit (%): Not Available

Autoignition Temp (°C): Not Available

State: Non Slump Paste

Boiling Range (°C): Not Available

Specific Gravity (water= 1): 1.5

pH (as supplied): 8

Vapour Pressure (kPa): Not Available

Evaporation Rate: Not Available

Flash Point (°C): >200

Upper Explosive Limit (%): Not Available

Decomposition Temp (°C): Not Available

Viscosity: Not Available

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

For incompatible materials - refer to Section 7 - Handling and Storage.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

» The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. The material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (eg. liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern.

EYE

» There is evidence that material may produce eye irritation in some persons and produce eye damage 24 hours or more after instillation. Severe inflammation may be expected with pain. There may be damage to the cornea. Unless treatment is prompt and adequate there may be permanent loss of vision. Conjunctivitis can occur

continued...

ARDEX WA RESIN W

Chemwatch Material Safety Data Sheet

Issue Date: 20-Feb-2009

NC317ECP

CHEMWATCH 16-3320

Version No:2.0

CD 2008/4 Page 8 of 14

Section 11 - TOXICOLOGICAL INFORMATION

following repeated exposure.

SKIN

» The material may cause moderate inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by redness, swelling and blistering.

Skin contact with the material may damage the health of the individual; systemic effects may result following absorption.

Open cuts, abraded or irritated skin should not be exposed to this material.

Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

INHALED

» There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.

CHRONIC HEALTH EFFECTS

» Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population.

There has been some concern that this material can cause cancer or mutations but there is not enough data to make an assessment.

Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.

There is some evidence that inhaling this product is more likely to cause a sensitisation reaction in some persons compared to the general population.

Based on experience with similar materials, there is a possibility that exposure to the material may reduce fertility in humans at levels which do not cause other toxic effects.

Glycidyl ethers can cause genetic damage and cancer.

4,4'-dihydroxyphenyl oxide may have effects similar to female sex hormones.

Bisphenol A may have effects similar to female sex hormones and when administered to pregnant women, may damage the foetus. It may also damage male reproductive organs and sperm.

TOXICITY AND IRRITATION

» unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

» Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested.

The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.

Oxiranes (including glycidyl ethers and alkyl oxides, and epoxides) exhibit many common characteristics with respect to animal toxicology. One such oxirane is ethyloxirane; data presented here may be taken as representative.

for 1,2-butylene oxide (ethyloxirane):

Ethyloxirane increased the incidence of tumours of the respiratory system in male and female rats exposed via inhalation. Significant increases in nasal papillary adenomas and combined alveolar/bronchiolar adenomas and carcinomas were observed in male rats exposed

continued...

ARDEX WA RESIN W

Chemwatch Material Safety Data Sheet

Issue Date: 20-Feb-2009

NC317ECP

CHEMWATCH 16-3320

Version No:2.0

CD 2008/4 Page 9 of 14

Section 11 - TOXICOLOGICAL INFORMATION

to 1200 mg/m³ ethyloxirane via inhalation for 103 weeks. There was also a significant positive trend in the incidence of combined alveolar/bronchiolar adenomas and carcinomas. Nasal papillary adenomas were also observed in 2/50 high-dose female rats with none occurring in control or low-dose animals. In mice exposed chronically via inhalation, one male mouse developed a squamous cell papilloma in the nasal cavity (300 mg/m³) but other tumours were not observed. Tumours were not observed in mice exposed chronically via dermal exposure. When trichloroethylene containing 0.8% ethyloxirane was administered orally to mice for up to 35 weeks, followed by 0.4% from weeks 40 to 69, squamous-cell carcinomas of the forestomach occurred in 3/49 males ($p=0.029$, age-adjusted) and 1/48 females at week 106. Trichloroethylene administered alone did not induce these tumours and they were not observed in control animals. Two structurally related substances, oxirane (ethylene oxide) and methyloxirane (propylene oxide), which are also direct-acting alkylating agents, have been classified as carcinogenic.

BISPHENOL A/ EPICHLOROHYDRIN RESIN:

» unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

Oral (rat) LD50: 13600 mg/kg

Oral (rat) LD50: 11400 mg/kg

Intraperitoneal (rat) LD50: 2400 mg/kg

Oral (mouse) LD50: 15600 mg/kg

Intraperitoneal (mouse) LD50: 4000 mg/kg

» Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested. The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.

for RTECS No: SL 6475000:

(liquid grade)

Equivocal tumourigen by RTECS criteria

Somnolence, dyspnea, peritonitis

IRRITATION

Nil Reported

Eye (rabbit): 100 mg - Mild

BISPHENOL F/ EPICHLOROHYDRIN COPOLYMER:

» unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

» Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested. The material may produce moderate eye irritation leading to inflammation. Repeated or

continued...

ARDEX WA RESIN W

Chemwatch Material Safety Data Sheet

Issue Date: 20-Feb-2009

NC317ECP

CHEMWATCH 16-3320

Version No:2.0

CD 2008/4 Page 10 of 14

Section 11 - TOXICOLOGICAL INFORMATION

prolonged exposure to irritants may produce conjunctivitis.

The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.

No significant acute toxicological data identified in literature search.

Data for liquid polymer, ie for molecular weights generally less than 700

CAUTION: Epoxy resin products may contain sensitising glycidyl ethers, even when these are not mentioned in the information given for the product.

Limited animal studies have indicated that bisphenol A diglycidyl ethers may be potential carcinogens. [CISDOC Patty]

(C12-14)ALKYLGLYCIDYL ETHER:

» unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

Oral (rat) LD50: 17000 mg/kg

Oral (rat) LD50: >10000 mg/kg

IRRITATION

Skin (rabbit): Moderate

Skin (human): Irritant

Skin (guinea pig): sensitiser

Skin (human): non- sensitiser

Eye (rabbit): Mild [Ciba]

Skin : Moderate

» Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested.

Oxiranes (including glycidyl ethers and alkyl oxides, and epoxides) exhibit many common characteristics with respect to animal toxicology. One such oxirane is ethyloxirane; data presented here may be taken as representative.

for 1,2-butylene oxide (ethyloxirane):

Ethyloxirane increased the incidence of tumours of the respiratory system in male and female rats exposed via inhalation. Significant increases in nasal papillary adenomas and combined alveolar/bronchiolar adenomas and carcinomas were observed in male rats exposed to 1200 mg/m³ ethyloxirane via inhalation for 103 weeks. There was also a significant positive trend in the incidence of combined alveolar/bronchiolar adenomas and carcinomas. Nasal papillary adenomas were also observed in 2/50 high-dose female rats with none occurring in control or low-dose animals. In mice exposed chronically via inhalation, one male mouse developed a squamous cell papilloma in the nasal cavity (300 mg/m³) but other tumours were not observed. Tumours were not observed in mice exposed chronically via dermal exposure. When trichloroethylene containing 0.8% ethyloxirane was administered orally to mice for up to 35 weeks, followed by 0.4% from weeks 40 to 69, squamous-cell carcinomas of the forestomach occurred in 3/49 males (p=0.029, age-adjusted) and 1/48 females at week 106. Trichloroethylene administered alone did not induce these tumours and they were not observed in control animals. Two structurally related substances, oxirane (ethylene oxide) and methyloxirane (propylene oxide), which are also direct-acting alkylating agents, have been classified as carcinogenic.

continued...

ARDEX WA RESIN W

Chemwatch Material Safety Data Sheet

Issue Date: 20-Feb-2009

NC317ECP

CHEMWATCH 16-3320

Version No:2.0

CD 2008/4 Page 11 of 14

Section 12 - ECOLOGICAL INFORMATION

Marine Pollutant: Not Determined

- » Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- » Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters. Wastes resulting from use of the product must be disposed of on site or at approved waste sites.
- » Significant environmental findings are limited. Oxiranes (including glycidyl ethers and alkyl oxides, and epoxides) exhibit common characteristics with respect to environmental fate and ecotoxicology. One such oxirane is ethyloxirane and data presented here may be taken as representative.

» for 1,2-butylene oxide (ethyloxirane):

Environmental fate: Ethyloxirane is highly soluble in water and has a very low soil-adsorption coefficient, which suggests that if released to water, adsorption of ethyloxirane to sediment and suspended solids is not expected. Volatilisation of ethyloxirane from water surfaces would be expected based on the moderate estimated Henry's Law constant. If ethyloxirane is released to soil, it is expected to have low adsorption and thus very high mobility. Volatilisation from moist soil and dry soil surfaces is expected, based on its vapour pressure. It is expected that ethyloxirane exists solely as a vapour in ambient atmosphere, based on its very high vapour pressure. Ethyloxirane may also be removed from the atmosphere by wet deposition processes, considering its relatively high water solubility.

Persistence: The half-life in air is about 5.6 days from the reaction of ethyloxirane with photochemically produced hydroxyl radicals which indicates that this chemical meets the persistence criterion in air (half-life of = 2 days)*.

Ethyloxirane is hydrolysable, with a half-life of 6.5 days, and biodegradable up to 100% degradation and is not expected to persist in water. A further model-predicted biodegradation half-life of 15 days in water obtained and used to predict the half-life of this chemical in soil and sediment by applying Boethling's extrapolation factors ($t_{1/2\text{water}} : t_{1/2\text{soil}} : t_{1/2\text{sediment}} = 1 : 1 : 4$) (Boethling 1995). According to these values, it can be concluded that ethyloxirane does not meet the persistence criteria in water and soil (half-lives = 182 days) and sediments (half-life = 365 days).

Experimental and modelled log Kow values of 0.68 and 0.86, respectively, indicate that the potential for bioaccumulation of ethyloxirane in organisms is likely to be low. Modelled bioaccumulation -factor (BAF) and bioconcentration -factor (BCF) values of 1 to 17 L/kg indicate that ethyloxirane does not meet the bioaccumulation criteria (BCF/BAF = 5000)*

Ecotoxicity:

Experimental ecotoxicological data for ethyloxirane (OECD 2001) indicate low to moderate toxicity to aquatic organisms. For fish and water flea, acute LC50/EC50 values vary within a narrow range of 70-215 mg/L; for algae, toxicity values exceed 500 mg/L, while for bacteria they are close to 5000 mg/L

* Persistence and Bioaccumulation Regulations (Canada 2000).

» DO NOT discharge into sewer or waterways.

Refer to data for ingredients, which follows:

BISPHENOL A/ EPICHLOROHYDRIN RESIN:

Marine Pollutant: Not Determined

- » Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- » Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters. Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

BISPHENOL F/ EPICHLOROHYDRIN COPOLYMER:

Marine Pollutant: Not Determined

- » Toxic to aquatic organisms.
- » Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters. Wastes resulting from use of the product must be disposed of on site or at approved waste sites.
- » May cause long-term adverse effects in the aquatic environment.

continued...

ARDEX WA RESIN W

Chemwatch Material Safety Data Sheet

Issue Date: 20-Feb-2009

NC317ECP

CHEMWATCH 16-3320

Version No:2.0

CD 2008/4 Page 12 of 14

Section 12 - ECOLOGICAL INFORMATION

(C12-14)ALKYLGLYCIDYL ETHER:

Marine Pollutant: Not Determined

» Toxic to aquatic organisms.

» Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters. Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

» May cause long-term adverse effects in the aquatic environment.

» Significant environmental findings are limited. Oxiranes (including glycidyl ethers and alkyl oxides, and epoxides) exhibit common characteristics with respect to environmental fate and ecotoxicology. One such oxirane is ethyloxirane and data presented here may be taken as representative.

» for 1,2-butylene oxide (ethyloxirane):

Environmental fate: Ethyloxirane is highly soluble in water and has a very low soil-adsorption coefficient, which suggests that if released to water, adsorption of ethyloxirane to sediment and suspended solids is not expected. Volatilisation of ethyloxirane from water surfaces would be expected based on the moderate estimated Henry's Law constant. If ethyloxirane is released to soil, it is expected to have low adsorption and thus very high mobility. Volatilisation from moist soil and dry soil surfaces is expected, based on its vapour pressure. It is expected that ethyloxirane exists solely as a vapour in ambient atmosphere, based on its very high vapour pressure. Ethyloxirane may also be removed from the atmosphere by wet deposition processes, considering its relatively high water solubility.

Persistence: The half-life in air is about 5.6 days from the reaction of ethyloxirane with photochemically produced hydroxyl radicals which indicates that this chemical meets the persistence criterion in air (half-life of = 2 days)*.

Ethyloxirane is hydrolysable, with a half-life of 6.5 days, and biodegradable up to 100% degradation and is not expected to persist in water. A further model-predicted biodegradation half-life of 15 days in water obtained and used to predict the half-life of this chemical in soil and sediment by applying Boethling's extrapolation factors ($t_{1/2\text{water}} : t_{1/2\text{soil}} : t_{1/2\text{sediment}} = 1 : 1 : 4$) (Boethling 1995). According to these values, it can be concluded that ethyloxirane does not meet the persistence criteria in water and soil (half-lives = 182 days) and sediments (half-life = 365 days).

Experimental and modelled log Kow values of 0.68 and 0.86, respectively, indicate that the potential for bioaccumulation of ethyloxirane in organisms is likely to be low. Modelled bioaccumulation -factor (BAF) and bioconcentration -factor (BCF) values of 1 to 17 L/kg indicate that ethyloxirane does not meet the bioaccumulation criteria (BCF/BAF = 5000)*

Ecotoxicity:

Experimental ecotoxicological data for ethyloxirane (OECD 2001) indicate low to moderate toxicity to aquatic organisms. For fish and water flea, acute LC50/EC50 values vary within a narrow range of 70-215 mg/L; for algae, toxicity values exceed 500 mg/L, while for bacteria they are close to 5000 mg/L

* Persistence and Bioaccumulation Regulations (Canada 2000).

Section 13 - DISPOSAL CONSIDERATIONS

• Containers may still present a chemical hazard/ danger when empty.

• Return to supplier for reuse/ recycling if possible.

Otherwise:

• If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.

• Where possible retain label warnings and MSDS and observe all notices pertaining to the product.

• DO NOT allow wash water from cleaning or process equipment to enter drains.

• It may be necessary to collect all wash water for treatment before disposal.

• In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.

• Where in doubt contact the responsible authority.

• Recycle wherever possible or consult manufacturer for recycling options.

• Consult State Land Waste Authority for disposal.

• Bury or incinerate residue at an approved site.

continued...

ARDEX WA RESIN W

Chemwatch Material Safety Data Sheet

Issue Date: 20-Feb-2009

NC317ECP

CHEMWATCH 16-3320

Version No:2.0

CD 2008/4 Page 13 of 14

Section 13 - DISPOSAL CONSIDERATIONS

- Recycle containers if possible, or dispose of in an authorised landfill.

Section 14 - TRANSPORTATION INFORMATION

» *Environmentally Hazardous Substances meeting the descriptions of UN 3077 or UN 3082 are not subject to this Code when transported by road or rail in;*

(a) *packagings;*

(b) *IBCs; or*

(c) *any other receptacle not exceeding 500 kg(L).*

- *Australian Special Provisions (SP AU01) - ADG Code 7th Ed.*

Labels Required: MISCELLANEOUS

HAZCHEM: ●3Z (ADG7)

Land Transport UNDG:

Class or division:	9	Subsidiary risk:	None
UN No.:	3082	UN packing group:	III
Shipping Name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains bisphenol A/ epichlorohydrin resin)		

Air Transport IATA:

ICAO/IATA Class:	9	ICAO/IATA Subrisk:	None
UN/ID Number:	3082	Packing Group:	III
Special provisions:	A97		
Shipping Name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. *(CONTAINS BISPHENOL A/ EPICHLOROHYDRIN RESIN)		

Maritime Transport IMDG:

IMDG Class:	9	IMDG Subrisk:	None
UN Number:	3082	Packing Group:	III
EMS Number:	F- A, S- F	Special provisions:	274 909 944
Limited Quantities:	5 L	Marine Pollutant:	Not Determined
Shipping Name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(contains bisphenol A/ epichlorohydrin resin)		

Section 15 - REGULATORY INFORMATION

POISONS SCHEDULE: S5

REGULATIONS

Regulations for ingredients

Ardex WA Resin W (CAS: None):

No regulations applicable

bisphenol A/ epichlorohydrin resin (CAS: 25068-38-6) is found on the following regulatory lists;

- Australia - Victoria Occupational Health and Safety Regulations - Schedule 9: Materials at Major Hazard Facilities (And Their Threshold Quantity) Table 2
- Australia Hazardous Substances
- Australia Inventory of Chemical Substances (AICS)
- Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Appendix E (Part 2)
- Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Appendix F (Part 3)
- Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Schedule 5
- OECD Representative List of High Production Volume (HPV) Chemicals

bisphenol F/ epichlorohydrin copolymer (CAS: 55492-52-9) is found on the following regulatory lists;

- Australia Inventory of Chemical Substances (AICS)
- GESAMP/EHS Composite List of Hazard Profiles - Hazard evaluation of substances transported by ships
- bisphenol F/ epichlorohydrin copolymer (CAS: 58421-55-9) is found on the following regulatory lists;
- Australia Inventory of Chemical Substances (AICS)
- bisphenol F/ epichlorohydrin copolymer (CAS: 9003-36-5) is found on the following regulatory lists;
- Australia Inventory of Chemical Substances (AICS)

(C12-14)alkylglycidyl ether (CAS: 68609-97-2) is found on the following regulatory lists;

- Australia Hazardous Substances

continued...

ARDEX WA RESIN W

Chemwatch Material Safety Data Sheet

Issue Date: 20-Feb-2009

NC317ECP

CHEMWATCH 16-3320

Version No:2.0

CD 2008/4 Page 14 of 14

Section 15 - REGULATORY INFORMATION

Australia Inventory of Chemical Substances (AICS)
OECD Representative List of High Production Volume (HPV) Chemicals

Section 16 - OTHER INFORMATION

INGREDIENTS WITH MULTIPLE CAS NUMBERS

Ingredient Name	CAS
bisphenol F/ epichlorohydrin copolymer	55492- 52- 9, 58421- 55- 9, 9003- 36- 5

» Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:
www.chemwatch.net/references.

» The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: 20-Feb-2009

Print Date: 20-Feb-2009

This is the end of the MSDS.